



DOWNLIGHT D6



DOWNLIGHT D6

The Downlight D6 is very easy to aim in all directions. The fixture is optimized around LED in different platforms: COMPACT|MICRO|NANO. All platforms have standard a 16, 24 and 36 degree optic. LED's can be delivered in CRI>80 and 90 and in colour temperature 2700|3000|4000 K.

VERSIONS

COMPACT









MICRO



NANO



DIMENSIONS



COLOURS

BLACK | WHITE | SILVER

LUMEN OUTPUT

LED 2000LM|2500LM|3000LM|3400LM

LED 1150LM|1500LM

LED 400LM|750LM|900LM

REFLECTORS

SPOT 12°|MEDIUM 24°|FLOOD 36°

ACCESSORIES

Honeycomb

STANDARD PORTFOLIO

COMPACT

D6-S C LED2900 830 WHITE
D6-S C LED2900 830 BLACK
D6-S C LED2900 830 SILVER

MICRO

D6-S M LED1500 830 WHITE
D6-S M LED1500 830 BLACK
D6-S M LED1500 830 SILVER

NANO

D6-S N LED900 830 WHITE
D6-S N LED900 830 BLACK
D6-S N LED900 830 SILVER

Spot

D6CSW2900S0097
D6CSB2900S0101
D6CSS2900S0105

D6MSW1500S0049
D6MSB1500S0053
D6MSS1500S0057

D6NSW900S0097
D6NSB900S0101
D6NSS900S0105

Medium

D6CSW2900M0098
D6CSB2900M0102
D6CSS2900M0106

D6MSW1500M0050
D6MSB1500M0054
D6MSS1500M0058

D6NSW900M0098
D6NSB900M0102
D6NSS900M0106

Flood

D6CSW2900F0099
D6CSB2900F0103
D6CSS2900F0107

D6MSW1500F0051
D6MSB1500F0055
D6MSS1500F0059

D6NSW900F0099
D6NSB900F0103
D6NSS900F0107

SYMBOLS



ELIO lighting B.V. | info@elio.lighting | www.elio.lighting